

AUTOMATIC HAND DRYERS

Top 10 Reasons to Consider ASI Hand Dryers

- 1. Energy Efficient
- 2. Powerful Thorough and fast drying
- 3. Classic Styling Looks great in every washroom
- 4. Sanitary All are no-touch operation
- 5. Cost Efficient No paper towels, less trash disposal
- 6. More ADA-Compliant Models &
- 7. Multiple Models and Finishes More choices
- **8. Easy Installation** Installs quickly with standard tools
- 9. **Durable** Backed by a warranty, up to 10 years
- 10. BAA Compliant All comply with the Buy American Act (BAA)







HIGH-SPEED AUTOMATIC HAND DRYERS

TRI-Umph™ HIGH-SPEED HAND DRYER







20200 TRI-Umph™ HIGH-SPEED HAND DRYER

Satin look cover: ABS plastic with silver ions. Ergonomic — No need to bend over or bend knees. Air blows down and back from vents on three sides. No water splash-back. Ultra hygienic — Over 99% of airborne bacteria is eliminated with the removable Super Filter System. 5-year warranty.



Decibel Level Min: 65 dB-A to 69.8 Max: dB-A @ 2M



Overall Dimensions: 1243/64" x 231/8" x 73/4" (322 x 588 x 197 mm)


ELECTRICAL SPECIFICATIONS:

Motor: 1 HP - 20 KRPM MAX - Brush type, dual ball bearings

Voltage: 110 - 272, 50/60 Hz. 1.2 kW

Heater: 450 Watts
Current: 10 Amps @ 110 VAC
DryTime: Approx. 12 seconds

- Ultra hygienic Over 99% of airborne bacteria and particles as small as 0.3 microns are eliminated with the removable Super Filter System:
 - » First Layer: HEPA filter» Second Layer: Carbon filter» Third Layer: Anti-microbial filter
- Anti-microbial silver ion treatment added to the ABS cover provides an additional layer of germ protection





Optional Ceramic Backplate for the TRI-Umph™ Hand Dryer

A0247 WALL PROTECTOR BACKSPLASH PLATE WITH FRAME

- Large absorbing/evaporating ceramic plate covers the wall directly behind the opening of the unit
- Plate matches the ceramic plate on hand dryer
- Installation can be retroactive

HIGH-SPEED AUTOMATIC HAND DRYERS

TURBO-Dri™ HIGH-SPEED HAND DRYERS





0197 TURBO-Dri™ SURFACE-**MOUNTED HIGH-SPEED AUTOMATIC HAND DRYER**

White is standard if no color is indicated. Optional finishes: Bright or Satin Stainless Steel (see chart on page 7). 5-year warranty.



0119 TURBO-Dri Semi-Recess Kit

Semi-recess kit reduces protrusion to less than 4", meeting both ADAAG and CalDAG Barrier-Free requirements.



Wall Opening: 10¾" × 16%" × 3¾" (273 x 416 x 95 mm) (min)

Decibel Level Min: 59 dB-A @ 2M Max: 72 dB-A @ 2M



Overall Dimensions: 81/16" x 1119/64" x 75/64" (205 x 287 x 180 mm)

ELECTRICAL SPECIFICATIONS:

1 HP - 7 - 18 KRPM - Adjustable, brush type, dual ball bearings Motor:

Voltage: 110 - 240 VAC, 50/60 Hz, 1.6 kW

400 - 900 Watts Heater: Current: 14.6 Amps @ 120 VAC Dry Time: Approx. 12 seconds

TURBO-ADA™ HIGH-SPEED HAND DRYER









0199 TURBO-ADA™ SURFACE-MOUNTED HIGH-SPEED AUTOMATIC HAND DRYER

White is standard if no color is indicated. Optional finishes: Bright or Satin Stainless Steel (see chart on page 7). 5-year warranty.



Decibel Level Max: 66.0 dB-A @ 2M

Overall Dimensions: 105%" x 815/32" x 4" (270 x 215 x 102 mm)

ELECTRICAL SPECIFICATIONS:

²/₃ HP - 16 - 29 KRPM - Adjustable, brush type, dual ball bearings Motor:

Voltage: 110 - 277 VAC, 50/60 Hz, 0.84 - 1.0 kW

325 - 450 Watts Heater: Current: 10.4 Amps @ 110 VAC Dry Time: **Under 15 Seconds**

HIGH-SPEED AUTOMATIC HAND DRYERS

TURBO-TUFF™ HIGH-SPEED HAND DRYER







0134 TURBO-TUFF $^{\text{TM}}$ FULLY RECESSED HIGH-SPEED AUTOMATIC HAND DRYER

Satin Stainless Steel (see chart on page 7). Vandal-resistant hand dryer is made of durable 18 gauge stainless steel cover with a satin finish and seamless design. Universal voltage. 5-year warranty.

Wall Opening: 125/16" x 153/16" x 37/8" (313 x 386 x 98 mm)

ELECTRICAL SPECIFICATIONS:

Motor: $\frac{2}{3}$ HP - 16 - 29 KRPM - Adjustable, brush type, dual ball bearings

Voltage: 115 - 277 VAC, 50/60 Hz, 5.2 - 10.4 kW

Heater: 325 - 450 Watts Current: 10.4 Amps @ 115 VAC **Dry Time: Under 15 Seconds**



Decibel Level Max: 66.0 dB-A @ 2M

TURBO-Dri™ JUNIOR HIGH-SPEED HAND DRYER



Decibel Level 69 dB-A @ 2M





0198 TURBO-Dri™ JUNIOR SURFACE-MOUNTED HIGH-SPEED AUTOMATIC HAND DRYER

White is standard if no color is indicated. Optional finishes: Bright or Satin Stainless Steel (see chart on page 7). 5-year warranty.

Overall Dimensions: $9^{25}\!/_{32}" \times 6^5\!/_{3}" \times 5^{13}\!/_{32}"$ (248 x 168 x 138 mm)

ELECTRICAL SPECIFICATIONS:

Motor: ²/₃ HP - 2900 RPM - Brush type, dual ball bearings

Voltage: 110 - 240 VAC, 50/60 Hz, 1.0 kW

Heater: 500 Watts

Current: 8.3 Amps @ 120 VAC; 4.2 Amps @ 240 VAC

Dry Time: Under 15 Seconds



ROVAL™ HAND DRYERS



0195 ROVAL™ CAST IRON COVER AUTOMATIC HAND DRYER WITH PORCELAIN ENAMEL FINISH

White is standard if no color is indicated. Optional Colors: Grey, Black, Almond (see chart on page 7). Universal voltage. 10-year warranty.

0185 ROVAL™ STEEL COVER AUTOMATIC HAND DRYER WITH PORCELAIN ENAMEL FINISH

White is standard if no color is indicated. Optional Colors: Grey, Black, Almond, Bright and Satin Stainless Steel (see chart on page 7). Universal voltage. 10-year warranty.





Decibel Level 63 dB-A @ 2M

SURFACE-MOUNTED 4" DEEP ADA DRYERS

0184 ROVAL™ SURFACE-MOUNTED **AUTOMATIC HAND DRYER**

277 VAC - 50/60 Hz. Ideal for school use.

0184/0185 Overall Dimensions: $14\frac{7}{16}$ " x $10\frac{13}{16}$ " x $3\frac{15}{16}$ " (367 x 275 x 100 mm) 0195 Overall Dimensions: 15³/₃₂" x 11⁷/₃₂" x 3 ¹⁵/₁₆" (383 x 285 x 100 mm)

ELECTRICAL SPECIFICATIONS:

Motor: 14 HP - 7500 RPM - Brush type, dual ball bearings

100 - 240 VAC, 50/60 Hz, 1.7 - 2.2 kW Voltage:

1857 Watts Heater:

17.6 Amps @ 115 VAC Current: **Dry Time: Under 25 Seconds**



Decibel Level 69 dB-A @ 2M

ROVAL™ HIGH-SPEED HAND DRYER

20199 ROVAL™ RECESSED HIGH-SPEED AUTOMATIC HAND DRYER

Satin Stainless Steel (see chart on page 7). This high performing hand dryer, with a drying time of less than 15 seconds, has a cover made of 18 gauge stainless steel and uniquely complements the Roval[™] Collection with its bowed face and gently radiused edges. 5-year warranty.

Wall Opening: (Conforms to ADA) 10½" x 15½" x 3¼" (267 x 384 x 83 mm)

ELECTRICAL SPECIFICATIONS:

3/3 HP - 2900 RPM - Brush type, dual ball bearings Motor:

Voltage: 110 - 240 VAC, 50/60 Hz, 1.0 kW

Heater: 500 Watts

8.3 Amps @ 120 VAC; 4.2 Amps @ 240 VAC Current:

Under 15 Seconds Dry Time:

AUTOMATIC HAND DRYERS



RECESSED COMBO THREE-IN-ONE



64674 RECESSED COMBO THREE-IN-ONE

Fully recessed ADA-compliant three-in-one paper towel dispenser with waste receptacle and high speed automatic hand dryer. Durable 14 gauge stainless steel cover has a satin finish and seamless design making it ideal for any washroom. 5-year warranty.

WALL OPENING: 12" x 541/4" H x 61/2" (305 x 1378 x 165 mm)

ELECTRICAL SPECIFICATIONS:

Motor: 3/3 HP - 2900 RPM - Brush type, dual ball bearings

Voltage: 110 - 240 VAC, 50/60 Hz, 1.0 kW

Heater: 500 Watts

Current: 8.3 Amps @ 120 VAC **Dry Time:** Under 15 Seconds



Decibel Level 69 dB-A @ 2M

FULLY RECESSED HAND DRYER

0133 FULLY RECESSED AUTOMATIC HAND DRYER

Fully recessed ADA-compliant hand dryer. Durable 14 gauge stainless steel cover has a satin finish and seamless design making it ideal for any washroom. Universal voltage. 10-year warranty.

Satin Stainless Steel (see chart on page 7).

Wall Opening: 14" x 16" x 4" (356 x 406 x 102 mm)

ELECTRICAL SPECIFICATIONS:

Motor: ¼ HP - 7500 RPM - Brush type, dual ball bearings

Voltage: 100 - 240 VAC, 50/60 Hz, 1.7 - 2.2 kW

Heater: 1857 Watts

Current: 17.6 Amps @ 115 VAC **Dry Time:** Under 25 Seconds





Decibel Level 63 dB-A @ 2M



AUTOMATIC HAND DRYERS

PROFILE™ HAND DRYER

0165 PROFILE™ COMPACT AUTOMATIC HAND DRYER

White is standard if no color is indicated. Optional Color: Grey (see chart below). Universal voltage. 10-year warranty.

Overall Dimensions: (Conforms to ADA) 11 %" x 11 ½2" x 3 ½" (289 x 285 x 99 mm)

ELECTRICAL SPECIFICATIONS:

1/4 HP - 7500 RPM - Brush type, Motor:

dual ball bearings

100 - 240 VAC, 50/60 Hz, 1.4 - 1.8 kW Voltage:

Heater: 1488 Watts

14.4 Amps @ 115 VAC Current: Dry Time: **Under 30 Seconds**

Decibel Level 64 dB-A @ 2M







Decibel Level 60 dB-A @ 2M

PORCELAIR HAND & FACE DRYERS

0141 PORCELAIR AUTOMATIC HAND & FACE DRYER

110-120 VAC 17 Amps

0144 PORCELAIR AUTOMATIC HAND & FACE DRYER

208-240 VAC 11 Amps

Adjustable blower for drying hands and face. White is standard if no color is indicated. Optional Colors: Grey, Black and Almond (see chart below). 10-year warranty.

Overall Dimensions:

 $9\frac{7}{16}$ " x $9\frac{41}{64}$ " x $6\frac{3}{8}$ " (240 x 245 x 162 mm)

ELECTRICAL SPECIFICATIONS:

Motor: 1/8 HP - 3150 RPM - Brushless type

dual ball bearings

100 - 240 VAC, 50/60 Hz, 1.6 - 2.1 kW Voltage:

Heater: 1704 Watts

15 Amps @ 120 VAC Current: 20 - 25 Seconds Dry Time:

FINISH/COLOR OPTIONS: White is standard if no color is indicated. (Printing limitations prohibit true color representation.)



40 Grey



41 Black



11 Almond



92 Bright Stainless Steel



93 Satin Stainless Steel

AUTOMATIC HAND DRYERS

AUTOMATIC HAND DRYERS WARRANTY: All component parts of all dryers shall be warranted to be free of defects in material and workmanship for a period of up to 10 years, except brushes which are warranted for 3 years.


ASI GUARANTEE

Products are guaranteed to be free from defects in workmanship and material for a period of one year from date of purchase. Any products returned under this guarantee will be repaired or replaced at no charge.

Illustrations and descriptions herein are applicable to production as of the date of this catalog. The manufacturer reserves the right to make changes and improvements in designs and dimensions at any time.

ADDITIONAL AMERICAN SPECIALTIES OFFERINGS:







Never Out Catalog



Visit americanspecialties.com for our complete line of washroom accessories

THE ASI GROUP

The ASI Group is your single source solution for Washroom Accessories, Toilet Partitions, Lockers and other storage products worldwide.

Partitions — The most complete line available in the industry — stainless steel, solid plastic, powder coated steel, phenolic, color-thru phenolic and plastic laminate partitions. Since 1957, we have offered designers worldwide a myriad of choices to satisfy every need.

Lockers — The best engineered lockers and shelving in the industry, period. A wide range of colors and materials (including steel, solid plastic and phenolic) offer the perfect solution for any storage application.

Our mission is to make our customers successful by providing value that exceeds price and an excellent service experience. We do this by providing superior design, the broadest range of quality products in the industry, and state-of-the art manufacturing to ensure that we have whatever our customers need, whenever they need it.

With experienced architectural representatives and customer service teams, we are here to help you deliver on projects that range from world-class office buildings, educational facilities, sports venues, and government buildings to hospitals, chain stores, and hospitality / entertainment complexes.

American Specialties, Inc., Global Partitions, Accurate Partitions Corp. and ASI Storage Solutions are all part of the ASI Group of companies.



