


FULLY-RECESSED AUTOMATIC HAND DRYER

Model # 0133



Simplicity Collection Hand Dryer

- Energy efficient with built-in infrared sensor for "ON" and "OFF"
- Crisp, clean, seamless styling
- Exposed surface is constructed of type 304 stainless steel
- Durable 14 gauge cover, 18 gauge hand drying recess and 20 gauge cabinet
- Satin finish on all exposed surfaces
- Fixed directional air vanes
- 10-year warranty
- ADAAG compliant 

Other Products in the Simplicity Collection Include...



Paper Towel Dispensers



Waste Receptacles



Toilet Seat
Cover Dispensers



Liquid Soap
Dispensers



SPECIFICATIONS

Recess Mounted Hand Dryer shall operate automatically from IR sensor that shall activate dryer when hands are placed in sensor zone. Cover shall be fabricated in one piece of 14 gauge thick type 304 stainless steel alloy 18-8. Hand drying recess shall be same grade in 18 gauge. All exposed surfaces shall have a satin finish and shall be protected during shipment by PVC film easily removable after installation. Cabinet shall be 20 gauge corrosion protected steel with a 1/2" wide perimeter trim to lay flush against wall and shall have flush pin-hex security screws to close cover. Motor and heating element shall have internal resetting automatic thermal protection. Fixed directional air vanes shall be heavy duty, rust proof and tamper resistant. Air intake slots shall not allow access to internal parts. Circuitry shall have self-adjusting time-out and fail-safe off protection controlled by a microprocessor that shall detect and reject false signals and shall automatically self-calibrate to provide uniform sensitivity over its entire life span. Entire unit shall be internally electrically grounded. Dryer unit shall have approval and be listed under the re-examination services of Underwriters Laboratories, Inc. Unit shall be warranted against defects in materials or workmanship for ten (10) years.

| RATINGS | | | | | | |
|---------|------|-------------------------------|----------------------------------------------------------|----------------------|----------------------|-----------------------------------------|
| MODEL | TYPE | TIMING | VOLTS HERTZ | AMPS | WATTS | COVER |
| 0133 | Hand | Automatic 4 Second hold on | 115 VAC 50/60 Hz 208 VAC 50/60 Hz 240 VAC 50/60 Hz | 17.6 15.9 18.3 | 2022 1654 2200 | No. 4 Satin finish vertical grain |

| MODEL | MOTOR | H/P | RPM | FAN TYPE | HEATING ELEMENT | AIR FLOW | OUTPUT |
|-------------|-------------------------------------|-----|------|-----------------------------|-------------------------------------------------------------------------|----------------------------------------------|--------------------------------------------------------------------------|
| 0133-115VAC | Brush Type Dual Ball Bearings | 1/4 | 7500 | Single Inlet Centrifugal | 1857 Watt Nichrome wire with auto reset circuit breaker @ 115 VAC | 185 CFM 314.5 m ³ /h | 149° F ± 5 @ 77° F (65° C ±2.8 @ 25° C) ambient room temp |
| 0133-208VAC | | | | | 1519 Watt Nichrome wire with auto reset circuit breaker @ 104 VAC | | |
| 0133-240VAC | | | | | 2020 Watt Nichrome wire with auto reset circuit breaker @ 240 VAC | | |



This handicap accessible logo indicates that a product meets the A.D.A. Accessibility Guidelines that products for use by the handicapped may be so located that the operative portion (i.e. push knob, towel slot) be no higher than 48" above the finished floor (AFF), tops of grab bars be between 36" and 33" and phone coin slots be no higher than 48" maximum from the floor.



American Specialties, Inc.
441 Saw Mill River Rd, Yonkers, NY 10701
Tel: 914.476.9000 Fax: 914.476.0688
E-mail: info@americanspecialties.com Web: americanspecialties.com